



Budenberg



Made in Britain

Unit B2, Stuart Road,
Altrincham Business Park,
Altrincham WA14 5GJ,
United Kingdom.

budenberg.co.uk
sales@budenberg.co.uk
+44 (0)161 777 7300

Model: 10N

The Model10N Needle Valves have been designed to give higher strength and integrity to instrument needle valves. Budenberg have incorporated a dynamic multi-ring gland system in the needle valve, which when combined with the anti blow-out back seating stem, guarantees resistance to all operating processes and pressures.

Low operating torques and high cycle life feature strongly in this unique Budenberg design, giving a "Low Cost of Ownership".

Key Benefits are:

100% gas tight seal under all conditions.

- Gland and stem leakage is a thing of the past due to the dynamic multi-ring gland system, combined with the anti blow-out back seating system
- Swaged self centering non-rotating stem tip in one material grade harder than the parent body material. This ensures a positive seat closure under all conditions.

Needle Valve Construction

Body Material

316 Stainless Steel to NACE as standard, other materials available

Standard Connection Sizes

1/2" NPT Female x Female

1/2" NPT Male x Female

Other thread sizes and types are available, please contact our sales office for details.

Standard Bore Sizes

Nominally 4mm to 6mm depending on connection size

Stem Packing

Multi stage 'dynamic' stem packing in PTFE / RPTFE to guarantee a gas tight seal under all conditions. Maximum Temperature of 240° C for PTFE packed units and 540° C for units packed with flexible graphite.

Certification Available

BS EN 10204 3.1b & 3.2 Material Certification

PMI and NDT Test Certification

Full range of certification and testing to suit the user requirements.

Guaranteed 2 times factor of safety

NEEDLE VALVE - PROCESS INDUSTRY



Needle Valve Features

Self centring, non rotating stem point

Vibration proof handle with positive location and excess torque break feature

Fire-safe designed to comply to BS6755 Pt2 & API-10497, API-607

Anti static, anti blow-out stem

Multi-stage 'dynamic' stem packing True 'metal to metal'

Body / Bonnet joint

Mechanically locked Valve Bonnet to prevent accidental removal


Max cold working pressure of 10,000 psi (10N)

All options available, full range of materials, thread types and sizes


Your Company name and model type etched on Valve body

Vented models available

Single Isolating Valves



**6 NF or 10NF
Female x Female**



**6 NM or 10NM
Male x Female**

Single Isolating Valve				
Model No	1/2" Male x 1/2" Female	L	A	Weight
10N8M8FS		92mm	90mm	0.65kg
10N8F8FS	1/2" Female x 1/2" Female	66mm	90mm	0.65kg

Options

For 6,000psi rating option, please replace the first "10" in the above model codes with "6"

Specifications and dimensions in this leaflet, are subject to change without prior notice.



Budenberg Gauge Co. Ltd.
Unit B2, Stuart Road,
Altrincham Business Park,
Altrincham WA14 5GJ,
United Kingdom.

Tel: +44 161 777 7300
Email: sales@budenberg.co.uk
Website: www.budenberg.co.uk

Budenberg Gauge Pvt. Ltd.
299-300, IInd Main Road,
Nehru Nagar,
Old Mahabalipuram Road (OMR),
Chennai - 600 096,
Tamil Nadu , India

Tel : +91 44 24541074
Tel/Fax: +91 44 24541075
Email: sales@budenberg-gauge.in

**Budenberg Gauge Asia
Pacific Ltd**

Unit 7A G/F Cheung Fat Ind
Bldg 64-76 Larch St Tai Kok
Tsui Kin
Hong Kong

Tel : +852 3709 0020
Email: sales@budenberg-gauge.asia

Budenberg Middle East LLC

PO Box 18980
Dubai
United Arab Emirates

Tel: +971 4 2511670
Email: sales@budenberg-me.org